

AMENDMENTS TO THE CLAIMS

Without prejudice, please amend the claims as reflected in the following listing of claims, which will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A communications unit comprising:
 - a) a first wireless transceiver port operable to communicate with a first wireless transceiver operable to conduct wireless communications with a wireless base station; and
 - b) a first expansion interface in communication with said first wireless transceiver port, and having a bus interface and operable to communicate with a second expansion interfaces of respective communications units on a plurality of communications on respective communications channels associated with respective said communications units, to permit any of said second communications units to access communicate with said wireless base station through the first wireless transceiver.
2. (Currently Amended) The communications unit of claim 1 wherein said first expansion bus interface is operable to conduct communications with said second communications unit on time multiplexed said communications channels.
3. (Currently Amended) The communications unit of claim 1 wherein said expansion bus interface is operable to conduct communications with the second communications unit on frequency multiplexed said communications channels.

4. (Original) The communications unit of claim 1 wherein said first wireless transceiver port and said first expansion interface are on a common base.
5. (Canceled)
6. (Currently Amended) The communications unit of claim 5 further comprising a first communications appliance interface operable to selectively communicate with at least one of the first wireless transceiver and said first expansion interface, to permit a communications appliance connected to said first communications appliance interface to communicate with the wireless base station or another communications unit in communication with said first expansion interface.
7. (Original) The communications unit of claim 6 wherein said first communications appliance interface includes an analog telephone interface.
8. (Original) The communications unit of claim 6 wherein said first wireless transceiver port, said first communications appliance interface and said first expansion interface are contained within a common base.
9. (Previously Presented) The communications unit of claim 6 wherein said first expansion interface and said first communications appliance interface are selectively operable to use said first wireless transceiver port.
10. (Previously Presented) The communications unit of claim 6 wherein said first expansion interface is operable to support independent communications between another communications unit and the wireless transceiver while supporting independent communications

between another communications unit and said first communications appliance interface.

11. (Previously Presented) The communications unit of claim 6 wherein said first expansion interface is programmable by commands received at said communications appliance interface.
12. (Currently Amended) The communications unit of claim 1 wherein said first expansion interface is programmable by commands received from at least one of said first wireless transceiver port and one of said ~~second~~ communications units.
13. (Previously Presented) The communications unit of claim 12 wherein said first expansion interface is programmable to cause said first wireless transceiver port to selectively communicate with one of a plurality of communications units operable to communicate with said first expansion interface.
14. (Previously Presented) The communications unit of claim 6 wherein said first expansion interface is programmable by commands received from a communications appliance in communication with said first communications appliance interface.
15. (Canceled)
16. (Currently Amended) The communications unit of claim ~~45~~1 wherein said bus interface includes a Pulse Code Modulation bus interface.
17. (Original) The communications unit of claim 1 wherein said first wireless transceiver port includes a receptacle operable to receive and hold a wireless telephone.

18. (Original) The communications unit of claim **1** wherein said first wireless transceiver port is operable to communicate with a data interface on a wireless telephone.

19. (Canceled)

20. (Previously Presented) The communications unit of claim **1** further comprising a processor circuit programmed to effect communications between said first wireless transceiver port and said first expansion interface.

21. (Previously Presented) The communications unit of claim **20** further comprising a communications appliance interface, said processor circuit being operable to effect communications between said first wireless transceiver port, said first expansion interface and said communications appliance interface.

22. (Previously Presented) The communications unit of claim **21** wherein said processor circuit is programmed to receive dialed digits from said communications appliance interface and communicate said dialed digits to said first wireless transceiver port to cause a transceiver in communication with said first wireless transceiver port to dial said dialed digits on a wireless network.

23. (Previously Presented) The communications unit of claim **22** wherein said processor circuit is programmed to communicate said dialed digits to said first wireless transceiver interface in response to a change in the rate at which dialed digits are received at said communications appliance interface.

24. (Previously Presented) The communications unit of claim **23** wherein said processor circuit is programmed to communicate said dialed digits

to said first wireless transceiver interface in response to expiry of a timeout period after entry of said dialed digits at said communications appliance.

25. (Currently Amended) A system for providing multiple access to a wireless transceiver, the system comprising:

a) a plurality of communications units, at least one of which includes:

i) a first wireless transceiver port operable to communicate with a first wireless transceiver operable to conduct wireless communications with a wireless base station; and

ii) a first expansion interface in communication with said first wireless transceiver port and having a bus interface operable to communicate with ~~said plurality of~~ expansion interfaces of respective communications units on a ~~plurality of~~ respective communications channels associated with respective said communications units, to permit any of said ~~plurality of~~ communications units to access communicate with said wireless base station through the first wireless transceiver.

26. (Original) The system of claim **25** wherein each of said communications units comprises a communications appliance interface operable to communicate with said first wireless transceiver port.

27. (Previously Presented) The system of claim **26** wherein at least some of the communications units have respective wireless transceiver ports

to said first wireless transceiver interface in response to expiry of a timeout period after entry of said dialed digits at said communications appliance.

25. (Currently Amended) A system for providing multiple access to a wireless transceiver, the system comprising:

a) a plurality of communications units, at least one of which includes:

i) a first wireless transceiver port operable to communicate with a first wireless transceiver operable to conduct wireless communications with a wireless base station; and

ii) a first expansion interface in communication with said first wireless transceiver port and having a bus interface operable to communicate with said plurality of expansion interfaces of respective communications units on a plurality of respective communications channels associated with respective said communications units, to permit any of said plurality of communications units to access communicate with said wireless base station through the first wireless transceiver.

26. (Original) The system of claim 25 wherein each of said communications units comprises a communications appliance interface operable to communicate with said first wireless transceiver port.

27. (Previously Presented) The system of claim 26 wherein at least some of the communications units have respective wireless transceiver ports

operable to be accessed by any of said communications appliance interfaces.

28. (Previously Presented) The system of claim 27 wherein any of said communications appliance interfaces can access any of said wireless transceivers, through respective expansion interfaces on respective communications units on which said any of said communications appliances are located and respective communications units on which any of said wireless transceivers are located.
29. (Previously Presented) The system of claim 27 wherein any of said communications units is operable to receive programming information from other communications units to configure said any of said communications units to selectively make its wireless transceiver port and its communications appliance interface communicate with a wireless transceiver port or a communications appliance interface of at least one other of said plurality of communications units.
30. (Currently Amended) A method of providing multiple access to a wireless transceiver, comprising supporting communications, through a first expansion interface, ~~on one of~~ having a bus interface configured to provide a plurality of communications channels, associated with respective communications units between a first wireless transceiver port of a first communications unit and ~~a second~~ at least one of said respective communications units, where and using said first wireless transceiver port ~~is operable to~~ communicate with a first wireless transceiver operable to conduct wireless communications with a wireless base station, to permit any of said communication units to communicate with said wireless base station through said first wireless transceiver.

31. (Currently Amended) The method of claim 30 wherein supporting communications comprises conducting communications with the ~~second~~at least one of said communications units on time multiplexed channels.

32. (Currently Amended) The method of claim 30 wherein supporting communications comprises conducting communications with the ~~second~~at least one of said communications units on frequency multiplexed channels.

33. (Original) The method of claim 30 wherein supporting communications comprises supporting communications between said first wireless transceiver port and said first expansion interface within a common base.

34. (Canceled)

35. (Currently Amended) The method of claim 30 further comprising selectively conducting communications between a first communications appliance interface and at least one of the first wireless transceiver and said first expansion interface, to permit a communications appliance connected to said communications appliance interface to communicate with the wireless base station or another communications unit in communication with said first expansion interface.

36. (Original) The method of claim 35 further comprising conducting communications with a telephone in communication with said first communications appliance interface.

37. (Previously Presented) The method of claim 35 further comprising selecting which of said first expansion interface and said first

communications appliance interface are to use said first wireless transceiver port.

38. (Previously Presented) The method of claim **35** further comprising simultaneously supporting independent communications between another communications unit and said wireless transceiver while supporting independent communications between another communications unit and said first communications appliance interface.
39. (Previously Presented) The method of claim **35** further comprising programming said first expansion interface by commands received at said communications appliance interface.
40. (Previously Presented) The method of claim **30** further comprising programming said first expansion interface by commands received from at least one of said first wireless transceiver port and said second communications unit.
41. (Currently Amended) The method of claim **40** further comprising programming said first expansion interface to cause said first wireless transceiver port to selectively communicate with one of a plurality of said communications units ~~operable to communicate with said first expansion interface~~.
42. (Previously Presented) The method of claim **35** further comprising programming said first expansion interface port by commands received from a communications appliance in communication with said first communications appliance interface.
43. (Canceled)

44. (Currently Amended) The method of claim ~~43~~30 wherein supporting communications comprises supporting communications through a Pulse Code Modulation bus interface.

45. (Currently Amended) The method of claim **30** further comprising receiving and holding a wireless telephone in a receptacle to facilitate connection of said wireless telephone to said wireless transceiver port.

46. (Original) The method of claim **30** further comprising causing said first wireless transceiver port to communicate with a data interface on a wireless telephone.

47. (Canceled)

48. (Original) The method of claim **30** further comprising receiving dialed digits from a communications appliance interface and communicating said dialed digits to said first wireless transceiver port to cause a transceiver in communication with said first wireless transceiver port to dial said dialed digits on a wireless network.

49. (Original) The method of claim **48** further comprising communicating said dialed digits to said first wireless transceiver interface in response to a change in the rate at which dialed digits are received at said communications appliance interface.

50. (Original) The method of claim **49** further comprising communicating said dialed digits to said first wireless transceiver interface in response to expiry of a timeout period after entry of said dialed digits at said communications appliance.

51. (Canceled)

- 52.** (Currently Amended) The method of claim ~~54~~30 further comprising supporting communications between a communications appliance interface on any of said communications units and said first wireless transceiver port.
- 53.** (Original) The method of claim **52** further comprising supporting communications between wireless transceiver ports on at least some of said communications units and communications appliance interfaces on at least some of said communications units.
- 54.** (Previously Presented) The method of claim **53** wherein supporting communications comprises causing respective expansion interfaces on respective communications units to permit any of said communications appliance interfaces to access any of said wireless transceivers.
- 55.** (Previously Presented) The method of claim **53** further comprising programming any of said communications units from other communications units to configure said any of said communications units to selectively make its wireless transceiver port and its communications appliance interface communicate with a wireless transceiver port or a communications appliance interface of at least one other of said plurality of communications units.
- 56.** (Previously Presented) The communications unit of claim **1** wherein said first wireless transceiver port is operable to communicate with a first wireless transceiver operable to conduct wireless communications with a wireless base station of a public network.
-